DATASHEET **HYFIRE TAURUS** SOUNDER VAD BASE (RED FLASH)

TAU-BSB-23R-01

The TAU-BSB-23R-01 Hyfire Taurus Sounder VAD base (red flash) is a high performance wireless device, incorporating an EN 54-23 compliant VAD used to alert people in the event of a fire. Each device has an integral moulded base for mounting a Taurus wireless detector or a sounder blanking cap if a detector is not required. The unit has as standard 32+32 recognised sounder tones (primary and secondary) and 4 levels of volume adjustment, as well as high power/low power visual settings, all of which can be easily configured on site. Powered by standard lithium batteries and utilising well proven adaptive radio signal processing algorithms ensure the highest levels of life safety and reliability.





KEY FEATURES

- Only compatible with Taurus detectors
- 32 tones settings (primary and secondary for alert and evacuation), selectable via onboard dip switches
- 4 volume levels
- Bi-directional wireless communications
- Can be used with Taurus addressable and conventional translators
- 22 pairs of field channels
- Dual channel redundancy
- Long communication range (\cong 1 km in open air)
- 5 year battery life (including weekly test)
- Utilises standard low-cost lithium battery technology
- Easy scan & link programming option
- Security screw to prevent tampering and unwanted removal
- 3rd party approval to EN54-3, EN54-23 and EN54-25
- Red and white blanking cap options
- 5 year product warranty

TECHNICAL INFORMATION





Hyfire Wireless Fire Solutions Ltd, Unit B12a, Holly Farm Business Park Honiley, Warwickshire CV8 1NP

T: +44(0) 1926 485 282 E: info@hyfirewireless.co.uk hyfirewireless.com

868 – 870 MHz Operating frequency range Max radiated power Weight (without batteries) 244 a Battery lifespan (typical) 5 years Operating Temperature Max humidity (non condensing) 95% RH Sound Output (typical)

TECHNICAL SPECIFICATION

VAD settings

Batteries

Dimensions

14dBm (25mW) 2x CR123A (3 V & 1.2 Ah) 129 mm x 54 mm -10°C to +55°C 88-91dBA (tone dependent) high power (C-3-15/ 0-4.6-15) low power (C-3-10)

STANDARDS & APPROVALS

- BS EN 54-3: Fire alarm devices
- BS EN-54-23: Visual Alarm
- devices



BS EN 54-25: Components using radio links and system requirements



DATASHEET HYFIRE TAURUS SOUNDER VAD BASE (RED FLASH)



BLANKING CAP OPTIONS





White blanking cap

Red blanking cap

T: +44(0) 1926 485 282 E: info@hyfirewireless.co.uk hyfirewireless.com

